

EASYFIX SR SLAT RUBBER



FEATURES

- ✓ New reinforced design
- ✓ High-grip profile
- ✓ DLG Signum approved
- ✓ Patented two-strip rubber system
- ✓ Suitable for Suding concrete slatted floors
- ✓ Sloped profile for quick urine run-off to increase drainage as well as reducing emissions
- ✓ Self-wedge solution - no additional fixings required

BENEFITS

- ✓ Increases animal comfort, welfare and confidence
- ✓ Reduces lameness
- ✓ Increases productivity - average daily weight gains for cattle
- ✓ Better feed conversion
- ✓ Suitable for use with scrapers

DIMENSIONS

- ✓ All Suding slatted floor sizes catered for



CONTACT

Suding Beton und Kunststoffwerk GmbH
Vestruper Str. 6, D - 49456, Lüsche

Tel: +49 (0) 5438/9410-0

EASYFIX Germany
Todtmooserstr. 43/1, D - 79664 Wehr

Tel: +49 (0) 7762/8059880

EASYFIX SDR SLAT RUBBER



FEATURES

- ✓ Smooth and sloped surface with slip strips
- ✓ Patented two strip rubber system with wedges
- ✓ Ribbed profile underside
- ✓ Custom sizes available for all Suding slat sizes

BENEFITS

- ✓ Softer for increased animal comfort and welfare
- ✓ Smooth & sloped surface to facilitate fast run off
- ✓ Reduces lameness
- ✓ Increases productivity - Average daily weight gains for cattle
- ✓ Better feed conversion
- ✓ Suitable for use with scrapers

DIMENSIONS

- ✓ All Suding slatted floor sizes catered for

EASYFIX MG ACTION



FEATURES

- ✓ Penny grip design
- ✓ Strong interlock on two sides
- ✓ Recessed holes around the edges facilitate stainless steel fixings
- ✓ Easy to clean with water or brush scraper
- ✓ Penny grip on underside so that mat can be inverted

BENEFITS

- ✓ Provides beef cattle with maximum grip and confidence
- ✓ Faster movement of animals
- ✓ Mats can be recessed into the concrete in new builds

DIMENSIONS

- ✓ Width: 305mm | 610mm | 915mm | 1220mm
- ✓ Length: 2235mm
- ✓ Depth: 18mm

CONTACT

Suding Beton und Kunststoffwerk GmbH
Vestruper Str. 6, D - 49456, Lüsche

Tel: +49 (0) 5438/9410-0

EASYFIX Germany
Todtmooserstr. 43/1, D - 79664 Wehr

Tel: +49 (0) 7762/8059880